







## CONTACT US AT (800) 824-8333 RAPTORWORKHOLDING.COM







Raptor began with an innovative design: the original, patented dovetail fixture. Now we have products that will either work independently or together seamlessly:



#### **Start with a Self Centering Vise.**

Use the vise in two ways:

- Hold a workpiece for dovetail prep.
- Machine a complete part.



#### Finish with a dovetailed Pinch Block.

Use these in a variety of applications:

- Machine the sixth side of workpiece for dovetail removal.
- Secondary or final machining operations.



#### Then utilize a patented Dovetail Fixture.

- The combination of the dovetail and springloaded clamping system provides superior holding strength.
- The dovetail prep on the bottom of a workpiece means full access to five sides of a workpiece with little waste.



#### **Raptor Tip**

Save time! Raptor's carbide dovetail cutters complete the dovetail prep, including the flat of the dovetail edge, in a single pass!

## THE BEST IN THE BUSINESS JUST BECAME EVEN STRONGER!

TE-CO/RAPTOR Workholding have entered into a partnership with PIRANHA to bring Swiss engineered precision Self-Centering Vises and versatile high pressure anodized aluminum Coolant Lines that withstand up to 80 bar (1160 psi) of pressure to the United States!









## **VISES**






## **DOVETAIL FIXTURES**



## **MULTI-FIXTURES**



# DOVETAIL CUTTERS & REPLACEMENT ITEMS



# ADAPTERS, RISERS, CONNECTORS & EXTENDERS



**PINCH BLOCKS** 

## **VISES**

#### **RWP-502**

100mm Self Center Vise

- All steel construction
- Automatically positions workpiece in center of vise. Centering tolerance is +/-0.013mm (0.0005") and repeatability is 0.001".
- Jaws adjust from either end of vise.
- Jaw clamping range is 0-2.500" as shown, and 2.500"-5.620" with jaws reversed.
- Jaw insert options available for a variety of holding applications: Dovetail, Serrated, Parallels, Soft Jaws, TalonGrip™ & Stops (all sold separately).
- Jaw accessory screws included (6) FHCS



#### **RWP-505**

150mm Self Center Vise

- All steel construction
- Automatically positions workpiece in center of vise. Centering tolerance is +/-0.013mm (0.0005") and repeatability is 0.001".
- Jaws adjust from either end of vise.
- Jaw clamping range is 0-3.870" as shown, and 4.75"-9.25" with jaws reversed.
- Jaw insert options available for a variety of holding applications: Dovetail, Serrated, Parallels,
   Soft Jaws, TalonGrip™ & Stops (all sold separately).
- Jaw accessory screws included (6) FHCS



Jaw Opening Standard: 0-3.88" / 98.4mm



## **VISE JAW INSERTS**

There are a variety of jaw inserts available to hold workpieces in place as illustrated below.

**RWP-1027** 

Soft Jaw (Right)

**RWP-1027-ST** 

Soft Jaw (Right)

**RWP-1028** 

Soft Jaw (Left)

**RWP-1028-ST** 

Soft Jaw (Left)

**RWP-1527** 

Soft Jaw (Right)

**RWP-1527-ST** 

Soft Jaw (Right)

**RWP-1528** 

Soft Jaw (Left)

**RWP-1528-ST** 

Soft Jaw (Left)

Vise Compatibility RWP-502

Material 6061 Aluminum

Vise Compatibility RWP-502

Material 1018 Steel

Vise Compatibility RWP-502

Material 6061 Aluminum

Vise Compatibility RWP-502

Material 1018 Steel

Vise Compatibility RWP-505

Material 6061 Aluminum

Vise Compatibility RWP-505

Material 1018 Steel

Vise Compatibility RWP-505

Material 6061 Aluminum

Vise Compatibility RWP-505

Material 1018 Steel



- Allows user to machine part specific profile in jaw for maximum clamping/location
- Good for secondary ops
- Dowel pins used for on/off repeatability

#### **RWP-1050**

Serrated 45° Dovetail Vise Compatibility RWP-502

**RWP-1550** 

Serrated 45° Dovetail Vise Compatibility RWP-505

- Use as a dovetail clamp or serrated edge clamp
- Utilizes dovetail form for secure clamping and retention
- Dovetail width can be modified to fit different workpiece sizes
- Utilizes standard 45° dovetail form, dovetail can be cut with any standard 45° cutter
- Bite height" = .110"
- Use serrated edged to "penetrate soft material workpiece"
- Hardened and ground steel
- Sold individually (need 2 per vise)



Standard Parallel (1/8" Ledge) Vise Compatibility RWP-502

#### **RWP-1551**

Standard Parallel (1/8" Ledge) Vise Compatibility RWP-505

- Provides precise straight edge for clamping machined workpiece
- Good for light / medium duty machining
- Rail provides maximum support while allowing clearance on bottom of workpiece
- Hardened and ground steel
- Sold individually (need 2 per vise)



Thin Parallel (1/16" Ledge) Vise Compatibility RWP-502

- Provides precise straight edge for clamping machined workpiece
- · Good for light / medium duty machining
- Rail provides support while allowing more clearance on bottom of workpiece
- Hardened and ground steel
- Sold individually (need 2 per vise)



#### **RWP-1056**

Straight Edge 60° Dovetail Vise Compatibility RWP-502

#### **RWP-1556**

Straight Edge 60° Dovetail Vise Compatibility RWP-505

- Utilizes dovetail for secure clamping and retention
- Dovetail width can be modified to fit various workpiece sizes
- Utilizes standard 60° dovetail form, dovetail can be cut with any standard 60° cutter
- Hardened and ground steel
- Sold individually (need 2 per vise)
- Recommended cutter: RWP-DC410C for material prep

#### **RWP-33020**

Mitee-Bite End Stop

- Locates workpiece for repeat positioning
- Fits both RWP-502 & RWP-505 vises

#### **RWP-33050**

Mitee-Bite TalonGrip™

- Low profile clamping
- Use to secure soft material workpieces
- Position flexibilty on insert slot of vise
- May be used in conjunction with end stop.
- Hardened steel
- Sold (2) per pack
- Fits both RWP-502 & RWP-505 vises



## **VISE ADAPTERS / RISER PLATES**

The following products were designed for the RWP-502 or RWP-505 vise. There are multiple options to choose from and will mount to most rotary table/pallets.

#### RWP-209-V100

#### **Emergency Adapter**

The emergency adapter allows you to drill the specific mounting hole configurations necessary to connect to your machine's rotary table/pallet. Once completed then connect adapter to table/pallet and mount the vise. When mounted together the overall height is 4.471". If additional height is needed, then mount the RWP-242-V100 Riser Plate in between vise and adapter for total Z: 6.221". RWP-PLUG-208 is available upon request (sold seperately).

Material Aluminum Plain Finish
Product Height 1.50" / 38.1 mm
Product Diameter 9.90" / 251.46mm

Vise Compatibility RWP-502

Boss/Hole 1.000" Diameter x .30" Receiving hole

Centering plug required. RWP-PLUG-208, sold separately and may need to be modified.



#### RWP-222-V100

#### **Universal Adapter**

Mount directly to your machine pallet or rotary table using T-slots. When mounted together the overall height is 4.971". If additional height is needed, then mount the RWP-242-V100 Riser Plate in between vise and adapter for total Z: 6.721". RWP-PLUG-208 is available upon request (sold separately).

Material 7075 Aluminum with Black Anodize Finish

Product Height 2.0" / 50.8mm

Product Diameter 9.875" / 250.825mm

Vise Compatibility RWP-502

Boss/Hole 1.000" Diameter x .30" Receiving hole

Centering plug required. RWP-PLUG-208, sold separately and may need to be modified.



#### RWP-223-V100

#### **Universal Adapter**

Mount directly to your machine pallet or rotary table using T-slots. When mounted together the overall height is 4.971". If additional height is needed, then mount the RWP-242-V100 Riser Plate in between vise and adapter for total Z: 6.721". RWP-PLUG-208 is available upon request (sold seperately).

Material 7075 Aluminum with Black Anodize Finish

Product Height 2.0" / 50.8mm

Product Diameter 11.90" / 302.26mm

Vise Compatibility RWP-502 & RWP-505

Boss/Hole 1.000" Diameter x .30" Receiving hole

Centering plug required. RWP-PLUG-208, sold separately and may need to be modified.



#### RWP-242-V100

#### Riser Plate

Mount directly to your machine pallet or rotary table. May also be used in a stacked application for higher Z, when mounted to either: RWP-209-V100, RWP-222-V100 or RWP-223-V100.

Material 7075 Aluminum with Black Anodize Finish

Product Height 1.75" / 44.45mm
Product Diameter 8.45" / 214.63mm

Vise Compatibility RWP-502

Mounting Info (4) C'Bores for ½-13 Or M12 SHCS on a 7.00" B.C.

Boss/Hole 1.000" Diameter x .30" Receiving hole

Centering plug required. RWP-PLUG-208, sold separately and may need to be modified.



#### RWP-251-V100

#### **Riser Plate**

Adapts RWP-502 vise to a Haas UMC750/UMC750ss, Matsuura MX520 300mm and other machines.

Material 7075 Aluminum with Black Anodize Finish

Product Height 4.50" / 114.3mm
Product Diameter 11.40" / 289.6mm

Vise Compatibility RWP-502

Mounting Info (8) C'Bores on a 9.92"/251.9mm for ½-13 Or M12 SHCS on a 7.00" B.C.

Will fit pallets with (4) or (6) T-slots

Boss/Hole 1.968"/50mm x .75" Receiving hole



#### RWP-244-V100

#### 2.25" Dovetail Connector Plate

This connector plate has been designed with a 2.25" dovetail base. Mounts directly to Raptor dovetail fixtures: RWP-006 or RWP-006SS. When mounting vise, dovetail connector plate, and dovetail fixture together, the total Z is 6.471".

The RWP-006(SS) connect to Raptors' standard adapters with 3.80" BC dia. interface: RWP-209 (total Z: 7.971"), RWP-222 (total Z:8.471"), RWP-223 (total Z:8.471").

Material 7075 Aluminum with Black Anodize Finish

Product Dimensions 6.5"L x 4.125" W x 1.0" H

165.1mm x 104.775mm x 25.4mm

Vise Compatibility RWP-502



Top View



**Bottom View** 



#### A FULL ACCESS PASS.

Speed up your manufacturing by machining five full sides of the workpiece in one set-up.

Raptor's patented dovetail design quickly locks the part in place for extreme clamping strength and rigidity without wasting much material on the base.

A locating pin ensures your part is positioned accurately and, unlike other products, the spring-loaded clamp can be tightened with a simple T-handle wrench. Quick and easy.

Raptor gets out of your way so you can get the job done.

#### **TESTED AND PROVEN.**

Raptor was created by manufacturers for manufacturers.

We know that workholding can be difficult because we face the same challenges. That is why we continue to create innovative products. Raptor is a strong, flexible workholding solution that has been utilized for years by some of the world's leading manufacturers. Raptor's dovetail design has been tested by an independent laboratory for strength.

#### **FASTER JOB SETUP.**

With Raptor, you can run a wide variety of parts and eliminate the changeover time. There is no need to spend time removing and replacing custom fixtures in your machines. We simplified the process. Smaller Raptor fixtures can also be attached to larger ones, allowing you to switch to any size part as fast as you can turn a hand tool. We've made workholding easier for you.

#### RAPTOR IS ADAPTABLE.

Our workholding products can fit any machine and any situation. We have a variety of adapters, risers, and fixtures built to attach directly to the most popular CNC machines. Multiple Raptors can be mounted to tombstones, bridges, carousels, nests and base plates. Raptor creates new products based on our customers' valuable feedback. If you need something special, let us know.

#### RAPTOR IS SIMPLE.

Simply load your workpiece onto the fixture and hand-tighten the spring-loaded clamp. Unloading is just as easy.



#### 1 - SIMPLE DOVETAIL

A simple workpiece prep creates a dovetail that locks into the Raptor spring-loaded clamp.



#### 2 - SPRING-LOADED CLAMP

Raptor's spring-loaded clamp strongly holds the part and makes releasing easy.





#### 3 - HAND TIGHTENED

Use a T-wrench to hand-tighten the clamp and you're done. It's quick, simple and strong.



#### 4 - STRONG BY DESIGN

Solid, super-strong stainless-steel or lightweight aluminum ensures that Raptor will hold up to repeated use.











#### **5 - FITS ANY MACHINE**

We have adapters, risers and versions of Raptor to fit any machine you can think of. Yes, even that one.



## 2.75" DOVETAIL FIXTURES



#### RWP-403SS-12

Stainless Steel 2.75" Dovetail Fixture

Max Workpiece Weight 225 Pounds / 102.058 kg Max Workpiece Size 10.0"L x 8.0"W x 10.0"H Steel

254mm x 203.2mm x 254mm

Fixture Material 17-4 Stainless Steel


Number of Clamps 3 Clamps

Clamp Replacement Kit RWP-KIT-3001SQ (2) required

Dovetail Height 0.25" / 6.35mm Dovetail Width 2.75" / 69.85mm Fixture Length 11.50" / 292.1mm Fixture Width 7.50" / 190.5mm Fixture Height 3.875" / 98.425mm Contact us for cutter recommendation.



## **2.25" DOVETAIL FIXTURES**



#### **RWP-006**

Aluminum 2.25" Dovetail Fixture



Max Workpiece Weight 80 Pounds / 36.287 kg Max Workpiece Size

8.0"L x 10.0"W x 10.0"H 254mm x 203.2mm x 254mm

Fixture Material 7075-T6511 Aluminum

**RWP-006SS** 

Stainless Steel 2.25" Dovetail Fixture



Max Workpiece Weight Max Workpiece Size Fixture Material

168 Pounds / 76.203 kg 12.0" / 304.8mm Cubed 17-4 Stainless Steel

Number of Clamps 2 Clamps Clamp Replacement Kit RWP-KIT-303SQ

Dovetail Height 0.1875" / 4.7625mm Dovetail Width 2.25" / 57.15mm

Fixture Dimensions 5.950"L x 3.957"W x 3.957"H

151.13mm x 100.5078 mm x 63.5mm


Bolt Circle Diameter 3.800" Raptor Interface

Recommended Cutter RWP-DC410C

Raptor Interface=(4) C'Bores on a 3.800" B.C. for ½-13 or M12 SHCS with a 1.250" x .250 Boss.

## **1.5" DOVETAIL FIXTURES**

The following fixtures are for parts using a dovetail width of 1.5 inches. These dovetail fixtures are available in multiple configurations constructed of aluminum or stainless steel.



Raptor Interface=(4) C'Bores on a 3.800" B.C. for ½-13 or M12 SHCS with a 1,250" x .250 Boss

#### **RWP-001**

Aluminum 1.5" Dovetail Fixture

## **RWP-001SS**

Stainless Steel 1.5" Dovetail Fixture



Number of Clamps 2 Clamps Clamp Replacement Kit RWP-KIT-301SQ Bolt Circle Diameter 3.800" Raptor Interface

Max Workpiece Weight 30 Pounds / 13.607 kg Max Workpiece Size 6.75" / 171.45mm Cubed Dovetail Height 0.125" / 3.175mm Dovetail Width 1.5" / 38.1mm Fixture Diameter 4.970" / 126.238mm Fixture Height 3.0" / 76.2mm



Fixture Material 7075-T6511 Aluminum

Fixture Material 17-4 Stainless Steel

#### **RWP-004**

Aluminum 1.5" Dovetail Fixture

This fixture is designed to fit to the Mori Seiki MNV3000 and Matsuura 330X (Metric pallet). It can also be utilized in other machines when connected with an adapter or riser.

Max Workpiece Weight 30 Pounds / 13.607 kg

Max Workpiece Size 6.75" / 171.45mm Cubed Fixture Material 7075-T6511 Aluminum

Number of Clamps 2 Clamps

Clamp Replacement Kit RWP-KIT-301SQ Dovetail Height 0.125" / 3.175mm Dovetail Width 1.5" / 38.1mm Fixture Diameter 4.970" / 126.238mm

Fixture Height 2.0" / 50.8mm

Bolt Circle Diameter 3.740" for ½-13 or M12 SHCS Boss/Hole 1.18" Diameter x .250" Boss



#### **RWP-013**

Aluminum 1.5" Dovetail Fixture



Fixture Material 7075-T6511 Aluminum

Number of Clamps 2 Clamps Clamp Replacement Kit RWP-KIT-301SQ Fixture Diameter 4.970" / 126.238mm Fixture Height 2.0" / 50.8mm Bolt Circle Diameter 3.800" Raptor Interface

Max Workpiece Weight 30 Pounds / 13.607 kg Max Workpiece Size 6.75" / 171.45mm Cubed Dovetail Height 0.125" / 3.175mm Dovetail Width 1.5" / 38.1mm



Stainless Steel 1.5" Dovetail Fixture

Fixture Material 17-4 Stainless Steel

**RWP-013SS** 

1-800-824-8333

#### Aluminum 1.5" Dovetail Fixture: 4" Diameter Bolt Circle

Made for tombstones with a 2.0" x 2.0" hole pattern or 4.0 bolt circle without a boss or plug.

This fixture will not mount to Raptors' adapters or risers.

Max Workpiece Weight 30 Pounds / 13.607 kg Max Workpiece Size 6.75" / 171.45mm Cubed Fixture Material 7075-T6511 Aluminum

Number of Clamps 2

Clamp Replacement Kit RWP-KIT-301SQ

Dovetail Height 0.125" / 3.175mm Dovetail Width 1.5" / 38.1mm

Bolt Circle Diameter 4.000"

Fixture Diameter 4.970" / 126.238mm

Fixture Height 3.0" / 76.2mm

Boss Hole None



#### **RWP-027**

#### Aluminum 1.5" Dovetail Fixture

This fixture is great for small rotary tables and lathes when used with a sub-plate. May also be used for the Yukiawa TNT100L when mounted to the RWP-241 adapter plate.

Max Workpiece Weight 20 Pounds / 9.071 kg 6.0" / 152.4mm Cubed Max Workpiece Size Fixture Material 7075-T6511 Aluminum

Number of Clamps 2

Clamp Replacement Kit RWP-KIT-301SQ

Dovetail Height 0.125" / 3.175mm Dovetail Width 1.5" / 38.1mm

Bolt Circle Diameter 2.362" / 60mm B.C. for 5/16 or M8 SHCS

Fixture Diameter 3.0" / 76.2mm Fixture Height 2.0" / 50.8mm

Boss Hole 1.000" Diameter x .30" Receiving hole

Centering plug required. RWP-PLUG-208, sold separately and may need to be modified.



#### **RWP-036SS**

#### Stainless Steel 1.5" Dovetail Fixture

Mount directly to the KME 135mm pallet used in the following KME products:

5 Axis Tombstones: 5 Axis Trunnions:

KME-TS300-2.0 300mm KME-TR100 KME-TS400-4.0 400mm KME-TR200 KME-TS500-4.0 500mm KME-TR300

Fixture Material 17-4 Stainless Steel

Number of Clamps 2

Clamp Replacement Kit RWP-KIT-301SQ

Dovetail Height 0.125" / 3.175mm Dovetail Width 1.5" / 38.1mm Fixture Diameter 5.315" / 135.001 mm

Fixture Height 2.0" / 50.8mm Bolt Circle Diameter 3.937"



#### **RWP-401-11**

#### Aluminum 11" Rail with 1.5" Dovetail

Max Workpiece Weight 140 Pounds / 63.502 kg Max Workpiece Size 17.0"L x 7.0"W x 12.0"H /

431.8mm x 177.8mm x 304.8mm

Fixture Material 7075-T6511 Aluminum

Number of Clamps

Clamp Replacement Kit RWP-KIT-301SQ (3) required

Dovetail Height 0.125" / 3.175mm 1.5" / 38.1mm 11.0" / 279.4mm Dovetail Width Fixture Length 4.40" / 111.76mm Fixture Width 3.0" / 76.2mm Fixture Height





## 0.75" DOVETAIL FIXTURES

The following fixtures are for parts using a dovetail width of 0.75 inches. These dovetail fixtures are available in multiple configurations constructed of aluminum or stainless steel.



Raptor Interface=(4) C'Bores on a 3.800" B.C. for ½-13 or M12 SHCS with a 1.250" x .250 Boss

#### **RWP-002**

0.75" Dovetail Fixture

#### **RWP-002SS**

0.75" Dovetail Fixture



Number of Clamps Clamp Replacement Kit Dovetail Height Fixture Diameter Fixture Height Bolt Circle Diameter

2 Clamps RWP-KIT-302SQ 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm 4.970" / 126.238mm 3.0" / 76.2mm 3.800" Raptor Interface



Max Workpiece Weight 18 Pounds / 8.164 kg Max Workpiece Size Fixture Material

5.75" / 146.05mm Cubed 7075-T6511 Aluminum

Max Workpiece Size

Max Workpiece Weight 25 Pounds / 11.339 kg 6.375" / 161.925mm Cubed Fixture Material 17-4 Stainless Steel

#### **RWP-003**

Aluminum 5C Collet Closer 0.75" Dovetail Fixture

Max Workpiece Weight 3 Pounds / 1.360 kg 3.0" / 76.2mm Cubed Max Workpiece Size Fixture Material 7075-T6511 Aluminum Number of Clamps 1 Clamp

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm Fixture Height 1.50" / 38.1mm

Clamp Replacement Kit RWP-KIT-302SQ

Fixture Inner Diameter 1.125" / 28.575mm Fixture Outer Diameter 2.230" / 56.642mm



#### **RWP-007SS**

Stainless Steel 0.75" Dovetail Fixture

Connects directly to System 3R 54mm pallets:

MacroStd: 3R-651.7E-S / 3R-651.7E-XS and MacroHP: 3R-651.7E.P, reducing downtime by switching to an alternate pallet in seconds.

Max Workpiece Weight 7 Pounds / 3.175 kg Max Workpiece Size 3.75" / 95.25mm Cubed Fixture Material 17-4 Stainless Steel

Number of Clamps 1 Clamp

Clamp Replacement Kit RWP-KIT-302SQ Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm

Fixture Dimensions 2.070"L x 2.070"W x 2.125"H

52.578mm x 52.578mm x 53.975mm



#### **RWP-011SS**

Stainless Steel 0.75" Dovetail Fixture with 0.75" Dovetail Bottom

Connects directly to compatible 0.75" dovetail fixtures allowing quick machining of smaller parts without removing the primary fixtures.

Max Workpiece Weight 7 Pounds / 3.175 kg Max Workpiece Size 3.75" / 95.25mm Cubed Fixture Material 17-4 Stainless Steel

Number of Clamps 1 Clamp

Clamp Replacement Kit RWP-KIT-302SQ

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm

Fixture Dimensions 2.070"L x 2.070"W x 2.001"H

52.578mm x 52.578mm x 50.825mm



#### **RWP-012SS**

Stainless Steel 0.75" Dovetail Fixture with 1.5" Dovetail Bottom

Connects directly to compatible 1.5" dovetail fixtures allowing quick machining of smaller parts without removing the primary fixtures.

Max Workpiece Weight 7 Pounds / 3.175 kg

Max Workpiece Size 3.75" / 95,25mm Cubed

Fixture Material 17-4 Stainless Steel

Number of Clamps 1 Clamp

Clamp Replacement Kit RWP-KIT-302SQ

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm

Fixture Dimensions 2.070"L x 2.070"W x 2.001"H

52.578mm x 52.578mm x 50.825mm



#### Aluminum 0.75" Dovetail Fixture

This fixture is designed to connect directly to the Haas TR110 and TRT-100 machines. It can also be utilized in other machines when connected with an adapter riser.

Max Workpiece Weight 18 Pounds / 8.164 kg Max Workpiece Size 5.75" / 146.05mm Cubed Fixture Material 7075-T6511 Aluminum Number of Clamps 2 Clamps

Clamp Replacement Kit RWP-KIT-302SQ Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm Fixture Diameter 4.330" / 109.982mm

Fixture Height 2.0" / 50.8mm

Bolt Circle Diameter 3.267" for (6) 5/16 or M8 SHCS Boss/Hole .4992" Diameter x .19" Boss



#### **RWP-023**

#### Aluminum 0.75" Dovetail Fixture: 4" diameter bolt circle

Made for Tombstones with a 2.0" X 2.0" Hole Pattern or 4.0 Bolt Circle - without a boss or plug. This fixture will not mount to Raptors' adapters or risers.

Max Workpiece Weight 18 Pounds / 8.164 kg Max Workpiece Size 5.75" / 146.05mm Cubed Fixture Material 7075-T6511 Aluminum

Number of Clamps 2

Clamp Replacement Kit RWP-KIT-302SQ

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm Fixture Diameter 4.970" / 126.238mm Fixture Height 3.0" / 76.2mm

Bolt Circle Diameter 4.0"

Boss/Hole None



#### **RWP-024**

#### Aluminum 0.75" Dovetail Fixture

#### **RWP-024SS**

Stainless Steel 0.75" Dovetail Fixture

Designed for modular applications. Multiple RWP-024 fixtures can be placed in-line to hold long parts. Multi-fixure options: RWP-024-2XR, RWP-024-3XR, RWP-024-4XR & RWP-024-6XC

Max Workpiece Weight 12.5 Pounds / 5.669 kg Max Workpiece Size 4.0" / 101.6mm Cubed Number of Clamps Clamp Replacement Kit Dovetail Height Fixture Dimensions

RWP-KIT-302SO 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm 2.0"L x 2.0"W x 1.5"H 50.8mm x 50.8mm x 38.1mm

Fixture Material 7075-T6511 Aluminum

Fixture Material 17-4 Stainless Steel \*EDM Screw Kits Available

#### Aluminum 6" Rail, with 0.75" Dovetail and 1.5" Dovetail Bottom

Designed for quick-change applications machining long and skinny parts.

Connects to compatible 1.5" dovetail fixtures.

Max Workpiece Weight 12.5 Pounds / 5.669 kg
Max Workpiece Size 8.0"L x 4.0"W x 4.0"H

203.2mm x 101.6mm x 101.6mm

Fixture Material 7075-T6511 Aluminum

Number of Clamps 3

Clamp Replacement Kit RWP-KIT-302SQ (2) required

Dovetail Height 0.125" / 3.175mm
Dovetail Width 0.75" / 19.05mm

Fixture Dimensions 6.0"L x 2.0"W x 1.5"H

152.4mm x 50.8mm x 38.1mm



#### **RWP-030SS**

#### Stainless Steel 0.75" Dovetail Fixture

Max Workpiece Weight 40 Pounds / 18.143 kg
Max Workpiece Size 7.5" / 190.5 Cubed
Fixture Material 17-4 Stainless Steel

Number of Clamps 3

Clamp Replacement Kit RWP-KIT-302SQ (2) required

Dovetail Height 0.125" / 3.175mm
Dovetail Width 0.75" / 19.05mm
Fixture Diameter 4.970" / 126.238mm
Fixture Height 3.0" / 76.2mm

Bolt Circle Diameter 3.800" Raptor Interface



#### **RWP-034SS**

#### Stainless Steel 0.75" Dovetail Fixture

This fixture is designed to connect directly to the Makino A51NX-5XU. It can also be utilized in other machines when connected with an adapter or riser.

Max Workpiece Weight 40 Pounds / 18.143 kg
Max Workpiece Size 7.5" / 190.5 Cubed
Fixture Material 17-4 Stainless Steel

Number of Clamps 3

Clamp Replacement Kit RWP-KIT-302SQ (2) required

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm

Bolt Circle Diameter 3.0"

Fixture Dimensions 5.0"L x 3.90"W x 2.0"H

127mm x 99.06mm x 50.8mm Boss/Hole 2.180" Diameter x .07" Boss



#### **RWP-038SS**

#### Stainless Steel 0.75" Dovetail Fixture

This fixture is designed to connect directly to either the HAAS TRT100 Compact Dual Axis Rotary Table or TR110 for milling applications. It can also be utilized in other machines when connected with an adapter or riser.

Max Workpiece Weight TRT100: 4 Lbs / TR100: 12 Lbs

Max Workpiece Size 5" / 127 Cubed
Fixture Material 17-4 Stainless Steel

Number of Clamps 2

Clamp Replacement Kit RWP-KIT-302SQ

Dovetail Height 0.125" / 3.175mm
Dovetail Width 0.75" / 19.05mm

Bolt Circle Diameter 3.267"

Fixture Diameter 4.330" / 109.982mm Fixture Height 1.3" / 33.02mm

Boss/Hole .4992" Diameter x .19" Boss



#### **RWP-405**

#### Aluminum 8" Rail with 0.75" Dovetail

Max Workpiece Weight 65 Pounds / 29.483 kg

Max Workpiece Size 4.0"L x 14.0"W x 4.0"H Steel

/ 101.6mm x 355.6mm x 101.6mm

Fixture Material 7075-T6511 Aluminum

Number of Clamps 4

Namber of Gramps

Clamp Replacement Kit RWP-KIT-302SQ (2) required

Dovetail Height 0.125" / 3.175mm
Dovetail Width 0.75" / 19.05mm
Fixture Dimensions 8.0"L x 3.8"W x 3.0"H


203.20mm x 96.52mm x 76.2mm





## **0.50" DOVETAIL FIXTURES**

The following fixtures are for parts using a dovetail width of 0.50 inches. These dovetail fixtures are available in multiple configurations constructed of aluminum or stainless steel.



Raptor Interface=(4) C'Bores on a 3.800" B.C. for 1/2-13 or M12 SHCS with a 1.250" x .250 Boss

#### **RWP-017SS**

#### Stainless Steel 0.50" Dovetail Fixture

Connects directly to System 3R 54mm pallets:

MacroStd: 3R-651.7E-S / 3R-651.7E-XS and MacroHP: 3R-651.7E.P, reducing downtime by switching to an alternate pallet in seconds.

Max Workpiece Weight 6 Pounds / 2.721 kg Max Workpiece Size 3.25" / 82.55 mm Cubed Fixture Material 17-4 Stainless Steel

Number of Clamps 1 Clamp

Clamp Replacement Kit RWP-KIT-306SQ (2) required

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.50" / 12.7mm

Fixture Dimensions 2.070"L x 2.070"W x 2.125"H

52.578mm x 52.578mm x 53.975mm



#### **RWP-018**

#### Aluminum 0.50" Dovetail Fixture

Number of Clamps

Boss/Hole 1.00" Diameter x .30 Receiving hole Max Workpiece Weight 10 Pounds / 4.535 kg Max Workpiece Size 4.75" / 120.65mm Cubed Fixture Material 7075-T6511 Aluminum

**RWP-018SS** 

Stainless Steel 0.50" Dovetail Fixture

2 Clamps Clamp Replacement Kit RWP-KIT-306SQ (2) required Dovetail Height 0.125" / 3.175mm Dovetail Width 0.50" / 12.7mm Fixture Diameter 4.970" / 126.238mm Fixture Height 3.0" / 76.2mm Bolt Circle Diameter 3.800" for (4) 1/2" or M12 SHCS

> Max Workpiece Weight 12 Pounds / 5.443 kg Max Workpiece Size

5.0" / 127mm Cube Fixture Material 17-4 Stainless Steel Raptor's plug RWP-PLUG-208SS, sold separately

#### **RWP-022SS**

#### Stainless Steel 0.50" Dovetail Fixture with 1.5" Dovetail Bottom

Connects to an RWP-001(SS), RWP-004, RWP-013(SS) or RWP-026.

Max Workpiece Weight 6 Pounds / 2.721 kg Max Workpiece Size 3.25" / 82.55 mm Cubed Fixture Material 17-4 Stainless Steel

Raptor's plug RWP-PLUG-208, sold separately.

Number of Clamps 1 Clamp

Clamp Replacement Kit RWP-KIT-306SQ (2) required

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.50" / 12.7mm

Fixture Dimensions 2.070"L x 2.070"W x 2.0"H

52.578mm x 52.578mm x 50.8mm



## **0.375" DOVETAIL FIXTURES**

0.375"

Stainless Steel 0.375" Dovetail Fixture

#### **RWP-019SS**

Stainless Steel 0.375" Dovetail Fixture



Clamp Replacement Kit RWP-KIT-305SQ Fixture Height 1.25" / 31.75mm

Fixture Material 17-4 Stainless Steel Dovetail Height 0.125" / 3.175mm Dovetail Width 0.375" / 9.525mm



Max Workpiece Weight 2 Pounds / 0.907 kg Max Workpiece Size Number of Clamps Fixture Length 2.5" / 63.5mm

2.50" / 63.5mm Cubed 1 Clamp

Max Workpiece Size

**RWP-042SS** 

4.0"L x 2.50"W x 2.50"H 101.6mm x 63.5mm x 63.5mm 2 Clamps

Number of Clamps

Fixture Length 3.75" / 95.25mm

#### **RWP-213SS**

Stainless Steel 0.75" Adapter for RWP-019SS only



Fixture Compatibility RWP-002(SS), RWP-015, RWP-023, RWP-024, RWP-030SS

#### **RWP-214SS**

Stainless Steel 1.5" Adapter for RWP-019SS only



Fixture Compatibility

RWP-001(SS), RWP-004, RWP-013(SS), RWP-026

#### **RWP-248SS**

Stainless Steel 0.75" Adapter for RWP-042SS only



Material 17-4 Stainless Steel

Height 0.5" / 12.7mm

Material 17-4 Stainless Steel Height 0.5" / 12.7mm


Adapter Length 2.5" / 63.5mm

Adapter Length 3.75" / 95.25mm

#### **RWP-249SS**

Stainless Steel 1.5" Adapter for RWP-042SS only

## 0.281" x 0.0781" **DOVETAIL FIXTURES**



#### **RWP-031SS**

Stainless Steel 0.281" Width x 0.0781" Height Dovetail Fixture with .75" Dovetail Bottom

Compatible fixtures: RWP-002, RWP-002SS, RWP-015, RWP-023, RWP-024 and RWP-030SS.

Max Workpiece Weight 0.284 Pounds / 0.128 kg Max Workpiece Size 1.25" / 31.75mm Cubed

Fixture Material 17-4 Stainless Steel

Number of Clamps 1 Clamp

Clamp Replacement Kit RWP-KIT-307SQ

Dovetail Width 0.281" / 7.137mm 

Recommended Cutter RWP-DC409C

This fixture replaces the discontinued RWP-010SS.





#### **RWP-032SS**

Stainless Steel 0.281" Width x 0.0781" Height Dovetail Fixture

Connects to your machine using the 4 mounting holes.

Max Workpiece Weight 0.284 Pounds / 0.128 kg 1.25" / 31.75mm Cubed Max Workpiece Size

Fixture Material 17-4 Stainless Steel

Number of Clamps 1 Clamp

Clamp Replacement Kit RWP-KIT-307SQ

Dovetail Width 0.281" / 7.137mm 

Recommended Cutter RWP-DC409C

This fixture replaces the discontinued RWP-009SS.




## **MODULAR FIXTURE COMPATABILITY**


The parts you machine come in different shapes and sizes, so we designed Raptor products with this in mind, to be versatile. To machine larger parts use a standard dovetail fixture. For smaller parts, mount a smaller dovetail fixture on top of a standard, as shown.

It's that easy. Spend time making parts, not figuring out how to hold them.

#### **0.75" MODULAR CONFIGURATIONS**




#### 1.50" MODULAR CONFIGURATIONS




## RAPTOR IS FAST.

Raptor multi-fixtures provide a platform to attach multiple Raptor dovetail fixtures. Now you can manufacture longer parts or program your 5-axis to machine multiple parts in one load.

Some Raptor multi-fixtures can attach to the top of other Raptor fixtures or adapters for quick and easy change-out. Load up the next multi-fixture with your workpieces while the other one is





#### **RWP-003-4X**

Aluminum 0.75" Dovetail Fixture - The Pyramid system holds 4 RWP-003 on a single base

This Raptor Pyramid utilizes four included RWP-003 0.75" dovetail fixtures. This is designed specifically for five-axis machining applications and allows you to hold four workpieces on a single base.

The RWP-003-4X Raptor Pyramind will mount to any of our standard adapters and risers.

> Max Workpiece Weight 3 Pounds / 1.360 kg Each Max Workpiece Size

3.0" / 76.2mm Cubed Each 7075-T6511 Aluminum

Fixture Material Number of Clamps 4 Clamps

Clamp Replacement Kit RWP-KIT-302SQ (2) required

Dovetail Height 0.125" / 3.175mm

Dovetail Width 0.75" / 19.05mm

Each Fixture Height 1.50" / 38.1mm

Total Product Height 3.25" / 82.55mm

Bolt Circle Diameter Boss / Plug

3.800" / 96.52mm Raptor Interface 1.250" Dia. x 0.25" / 31.75mm x 6.35mm



#### RWP-019-4X45T

Stainless Steel 0.375" Dovetail Fixture - The pyramid system holds 4 RWP-019SS on a single base

This Raptor Pyramid utilizes four included RWP-019SS 0.375" dovetail fixtures mounted at a 45 degree angle. This Raptor Pyramid has a 1.5" dovetail bottom and attaches to the top of other Raptor fixtures for quick and easy change-out. Load up the next pyramid with your workpieces while the other one is cycling. Changeover time is reduced and the productivity of your machine is drastically increased.

The RWP-019-4X45T Raptor mini tombstone will mount the any fixture with a 1.5" dovetail.

Max Workpiece Weight 2 Pounds / 0.907 kg Each

Max Workpiece Size 2.50" / 63.5mm Cubed Each Fixture Material 17-4 Stainless Steel Fixtures Aluminum Base

Number of Clamps 4 Clamps

Clamp Replacement Kit RWP-KIT-305SQ (2) required

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.375" / 9.525mm Each Fixture Height 1.25" / 31.75mm Total Product Height 2.69" / 68.326mm



#### RWP-019-4X90T

Stainless Steel 0.375" Dovetail Fixture - The Mini Tombstone system holds 4 RWP-019SS on a single base

This Raptor Mini Tombstone utilizes four included RWP-019SS 0.375" dovetail fixtures mounted at a 90 degree angle. This Raptor Mini Tombstone has a 1.5" dovetail bottom and attaches to the top of other Raptor fixtures for quick and easy change-out. Load up the next Mini Tombstone with your workpieces while the other one is cycling. Changeover time is reduced and the productivity of your machine is drastically increased.

The RWP-019-4X90T Raptor mini tombstone will mount the any fixture with a 1.5" dovetail.

Max Workpiece Weight Max Workpiece Size


2 Pounds / 0.907 kg Each 2.50" / 63.5mm Cubed Each Fixture Material 17-4 Stainless Steel Fixtures Aluminum Base

Number of Clamps 4 Clamps

Clamp Replacement Kit RWP-KIT-305SQ (2) required

Dovetail Height 0.125" / 3.175mm Each Fixture Height 1.25" / 31.75mm Total Product Height 3.13" / 79.502mm

Dovetail Width 0.375" / 9.525mm



#### RWP-042-4X90T

Stainless Steel 0.375" Dovetail Fixture - The Mini Tombstone system holds 4 RWP-042SS on a single base

This Raptor Mini Tombstone utilizes four included RWP-042SS 0.375" dovetail fixtures mounted at a 90 degree angle. This Raptor Mini Tombstone has a 1.5" dovetail bottom and attaches to the top of other Raptor fixtures for quick and easy change-out. Load up the next Mini Tombstone with your workpieces while the other one is cycling. Changeover time is reduced and the productivity of your machine is drastically increased.

The RWP-042-4X90T Raptor mini tombstone will mount the any fixture with a 1.5" dovetail.

Max Workpiece Weight 7 Pounds / 3.47 kg Each Max Workpiece Size


4.0" L x 2.50" W x 2.50" H Fixture Material 17-4 Stainless Steel Fixtures Aluminum Base

Number of Clamps 4 Clamps Clamp Replacement Kit RWP-KIT-305SQ (4) required

Dovetail Height 0.125" / 3.175mm

Dovetail Width 0.375" / 9.525mm

Each Fixture Height 1.25" / 31.75mm Total Product Height 4.38" / 111.252mm



#### **RWP-024-2XR**

Aluminum 0.75" Dovetail Fixture - In-Line bridge system holds 2 RWP-024 on a single base

The RWP-024-2XR is a 0.75" dovetail bridge system for milling applications. This product is designed for modular applications: utilizing two RWP-024 0.75" fixtures in-line to hold longer parts.

Fixture Material

7075-T6511 Aluminum

Number of Clamps

2 Clamps

Clamp Replacement Kit RWP-KIT-302SQ

Dovetail Height 0.125" / 3.175mm

Dovetail Width 0.75" / 19.05mm

Fixture Height 2.875" / 73.025mm

Base Length 7.0" / 177.8mm

1 Workpiece (Total)

Max Workpiece Weight Max Workpiece Size

16 Pounds / 7.257 kg 8.5"L x 4.0"W x 4.0"H

215.9mm x 101.6mm x 101.6mm



#### 2 Workpieces (Each)

8 Pounds / 3.628 kg 4.0" / 101.6mm Cubed

#### RWP-024-3XR

Aluminum 0.75" Dovetail Fixture - In-Line bridge system holds 3 RWP-024 on a single base

The RWP-024-3XR is a 0.75" dovetail bridge system for milling applications. This product is designed for modular applications: utilizing three RWP-024 0.75" fixtures in-line to hold longer parts.

Fixture Material 7075-T6511 Aluminum

Number of Clamps 3 Clamps

Clamp Replacement Kit RWP-KIT-302SQ (2) required

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm Fixture Height 2.875" / 73.025mm Base Length 10.0" / 254mm



#### 1 Workpiece (Total)

Max Workpiece Size

Max Workpiece Weight 24 Pounds / 10.886 kg 12.5"L x 4.0"W x 4.0"H

317.5mm x 101.6mm x 101.6mm

8 Pounds / 3.628 kg 4.0" / 101.6mm Cubed

#### **RWP-024-4XR**

Aluminum 0.75" Dovetail Fixture - In-Line bridge system holds 4 RWP-024 on a single base

The RWP-024-4XR is a 0.75" dovetail bridge system for milling applications. This product is designed for modular applications: utilizing four RWP-024 0.75" fixtures in-line to hold longer parts.

Fixture Material 7075-T6511 Aluminum

Number of Clamps 4 Clamps

Clamp Replacement Kit RWP-KIT-302SQ (2) required

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm Fixture Height 2.875" / 73.025mm Base Length 13.0" / 330.2mm

#### 1 Workpiece (Total)

Max Workpiece Weight Max Workpiece Size 32 Pounds / 14.514 kg 16.5"L x 4.0"W x 4.0"H

419.1mm x 101.6mm x 101.6mm



#### 4 Workpieces (Each)

8 Pounds / 3.628 kg 4.0" / 101.6mm Cubed

#### **RWP-024-6XC**

#### Aluminum 0.75" Dovetail Fixture - 6 Fixture Carousel

The RWP-024-6XC is a 0.75" dovetail carousel for milling applications. This product is designed for modular applications: utilizing 6 RWP-024 fixtures on a carousel base to machine multiple items in 1 operation. This carousel base mounts to either RWP-006 or RWP-006SS

Max Workpiece Weight Max Workpiece Size

Fixture Material Number of Clamps

Clamp Replacement Kit

8 Pounds / 3.628 kg 4.0" / 101.6mm Cubed

7075-T6511 Aluminum 1

RWP-KIT-302SO (3) required

Dovetail Height 0.125" / 3.175mm Dovetail Width 0.75" / 19.05mm Fixture Height 1.5" / 38.1mm





## **NEED DOVETAIL CUTTERS?**

We have a solution for that too. Raptor dovetail cutters machine the flat on the dovetail edge of your workpiece in one pass. This prevents a sharp edge on the dovetail from pressing into the corner of the fixture. Our dovetail cutters are available in a variety of dovetail heights and diameters depending on your need.

#### RWP-DC403U

3 Flute Uncoated 0.75" Dia.

0.125" High Dovetail Cutter Works well with aluminum or softer materials. Works well with 1.50, .750. .500 & .375 dovetail sizes.

#### RWP-DC407C

4 Flute Coated 0.35" Dia.

0.125" High Dovetail Cutter Designed for prolonged life & for harder materials. Works well with 1.50, .750, .500 & .375 dovetail sizes.

#### RWP-DC404C

4 Flute Coated 0.75" Dia.

0.125" High Dovetail Cutter Designed for prolonged life & for harder materials. Works well with 1.50, .750, .500 & .375 dovetail sizes.

#### **RWP-DC408C**

4 Flute Coated 0.45" Dia.

0.125" High Dovetail Cutter Designed for prolonged life & for harder materials. Works well with 1.50, .750, .500 & .375 dovetail sizes.

#### RWP-DC405C

4 Flute Coated 0.248" Dia.

0.0469" High Dovetail Cutter Designed for prolonged life & for harder materials. Works well with .281 X .046 dovetail size (old style).

#### RWP-DC409C

4 Flute Coated 0.248" Dia.

0.0781" High Dovetail Cutter Designed for prolonged life & for harder materials. Works well with .281 X .0781 dovetail (current style).

#### RWP-DC410C

4 Flute Coated 0.75" Dia.

0.750" Shank, 0.138" High Dovetail Cutter Designed for prolonged life & for harder materials. Works well with 2.25" dovetail size.

See website for Speeds & Feed Rates for Raptor Dovetail Cutters.

## REPLACEMENT PARTS

#### RWP-KIT-301SQ

Replacement Clamp Kit

Fits 1.500" Dovetail size. (2) Clamp assemblies per kit.

#### **RWP-KIT-303SQ**

Replacement Clamp Kit

Fits 2.250" Dovetail size. (2) Clamp assemblies per kit.

#### RWP-KIT-306SQ

Replacement Clamp Kit

Fits .500" Dovetail size. (2) Clamp assemblies per kit.

#### **RWP-KIT-302SO**

Replacement Clamp Kit

Fits .750" Dovetail size. (2) Clamp assemblies per kit.

#### RWP-KIT-304SQ

Replacement Clamp Kit

Fits .281" X .0461 Dovetail size. (2) Clamp assemblies per kit.

#### RWP-KIT-307SQ

Replacement Clamp Kit

Fits .281" X .0781 Dovetail size. (2) Clamp assemblies per kit.



#### RWP-KIT-305SQ

Replacement Clamp Kit

Fits .375" Dovetail size. (2) Clamp assemblies per kit.

#### **RWP-KIT-3001SQ**

Replacement Clamp Kit

Fits 2.75" Dovetail size. (2) Clamp assemblies per kit.

#### RWP-PLUG-208

Blank 2.500" Diameter allows customer to modify to fit specific application. Precision 1.000" Diameter fits in the bottom of fixtures/risers that have a Raptor interface.



#### **RWP-8-32**

8/32 x 1/4 Replacement Locating Pins

These replacement locating pins are for all Raptor Fixtures except the RWP-019SS and RWP-042SS.

Five replacement pins per pack.

These are for fixtures that were manufactured before 2017.











#### RWP-8-32CLS

8/32 x 1/4 Replacement Locating Pins

These replacement locating pins are for all Raptor Fixtures except the RWP-019SS and RWP-042SS.

These are for fixtures that were manufactured 2017 or after. Five replacement pins per pack.











#### RWP-8-32M0

8/32 x 8/32 x .165 Replacement Locating Pins

These replacement locating pins are for the RWP-019SS and RWP-042SS only.

Five replacement pins per pack.












## RAPTOR IS FLEXIBLE.

The parts you make come in different sizes and so does Raptor. Our Micro-Raptors work great for small parts while our Raptor Rails, Raptor Nests and Raptor Tombstone solutions can hold multiple parts or workpieces as heavy as 150 pounds.



## RAPTOR IS ADAPTABLE.



Our workholding products can fit any machine and any situation. We have a variety of adapters, risers, and fixtures built to attach directly to the most popular CNC machines. Multiple Raptors can be mounted to tombstones, multi- fixtures and base plates.

Raptor creates new products based on our customers' valuable feedback. If you need something special, let us know.

#### **RWP-202**

**Adapter** 

Enables compatible fixtures to be mounted on the Haas TR210, HRT210 & HRC210

Material 7075-T6511 Aluminum
Product Height 2.0" / 50.8mm
Product Diameter 8.20" / 208.28mm
Bolt Circle Diameter 6.50" / 165.1mm
Connection Bolts (6) 1/2" SHCS

Boss / Hole 2.000" Dia x .375" Boss Mounts All Fixtures with Raptor interface



#### **Adapter**

Enables compatible fixtures to be mounted on the following Haas machines: TR160, TR160-2, TR200Y, HRT160 & TRT160.

Material 7075-T6511 Aluminum

Product Height 1.5" / 38.1mm Product Diameter 6.30" / 160.02mm Bolt Circle Diameter 5.40" / 137.16mm Connection Bolts (6) 3/8" SHCS T-NUTS Boss / Hole 1.499" Dia x 0.313" Boss

Mounts All Fixtures with Raptor interface



#### **RWP-206**

#### Riser for Mori Seiki NMV3000

While supplies last. Replaced by Universal Riser RWP-262. For metric pallet see Universal Riser RWP-262.

Enables compatible fixtures to be mounted on the Mori Seiki NMV3000.

Material 7075-T6511 Aluminum

Product Height 3.5" / 88.9mm Product Diameter 8.980 / 228.092mm

Bolt Circle Diameter 175mm (RWP-205) / 7.0" (RWP-206)

Connection Bolts (4) M12 SHCS (RWP-205) / (4) 1/2" SHCS (RWP-206)

Boss / Hole 1.180" Dia x 0.250 Boss Connects to Mori Seiki NMV3000



#### **RWP-262**

#### Medium Universal Riser

Enables compatible fixtures to be mounted to multiple machines.

Material 7075-T6511 Aluminum

Product Height 3.5" / 88.9mm Product Diameter 8.980 / 228.092mm Bolt Circle Diameter 6.000 to 7.030 range Connection Bolts 1/2-13 or M12 SHCS

> Boss / Hole 1.000" Dia x 0.30" Receiving hole Connects to Mori Seiki NMV5000, DMU50/50eco,

> > NMV3000 Metric/English & multiple other machines

Mounts All Fixtures with Raptor interface

\*Raptor's plug RWP-PLUG-208, sold separately, may need to be modified.



#### **Emergency Adapter**

Emergency adapter plate enables any compatible fixtures to be mounted on the pallet of your machine. You simply add the mounting holes.

Material 6061 Aluminum
Product Height 1.5"/38.1mm
Product Diameter 7.950" / 201.93mm

Boss / Hole 1.000" Dia x 0.30" Receiving hole

Connects to Any Machine

Mounts All Fixtures with Raptor interface

\*Raptor's plug RWP-PLUG-208, sold separately, may need to be modified.



#### **RWP-209**

#### **Emergency Adapter**

Emergency adapter plate enables any compatible fixtures to be mounted on the pallet of your machine. You simply add the mounting holes.

Material 6061 Aluminum Product Height 1.5" / 38.1mm

Product Diameter 9.055" / 229.997mm

Boss / Hole 1.000" Dia x 0.30" Receiving hole

Connects to Any Machine

Mounts All Fixtures with Raptor interface

\*Raptor's plug RWP-PLUG-208, sold separately, may need to be modified.



#### **RWP-239**

#### **Small Machine Adapter**

Small adapter allows RWP-024 and RWP-024SS (.75" Dovetail), RWP-019SS and RWP-042SS (.375" Dovetail) to be adapted to the following machines: Haas TRT70 & TRT100, Nikken 100FA & 130FA, Yukiwa TNT100L, Sankyo RT80 & RT100 and others.

Material 6061 Aluminum with Blue Anodize Finish

Product Height .75" / 19mm
Product Diameter 3.940 / 100mm

Boss / Hole .3755" Dia x .38" Receiving hole Includes Centering plug .375" Dia. with 2.50"

Blank machinable diameter and a 3/8" x .75 LG dowel pin



There are many CNC machines and rotary table sizes. That's why we offer universal adapters. Our universal adapters are 2 inches tall and are available in 9 inch and 11 inch diameters. Both universal adapters have multiple mounting slots so they are guaranteed to fit your machine.

Combine the universal adapters with extenders available in either 1 inch or 2 inch sizes to provide additional height without unnecessary bulk. Please refer to charts for options.

#### **RWP-222**

#### Universal Adapter 9.875" Diameter, 2" Height

Has multiple slots to allow for use on multiple machine pallets or rotary tables. This universal adapter is modular in design with many options

Material 7075 Aluminum with Black Anodized Finish

Product Height 2.0" / 50.8mm

Product Diameter 9.875" / 250.825mm


Bolt Circle Diameter T-Slots for 3/8" or M10 SHCS on 5.50"-8.50"/139.7mm-215.9mm B.C.

Connection Bolts (4) 1/2"-13 UNC-2B

Boss / Hole 1.00" Dia x 0.30" Receiving Hole
Connects to RWP-206, RWP-601, RWP-602
Mounts All Fixtures with Raptor interface

RAPTOR

#### **RWP-222 Universal Adapter Configuration Options**



<sup>\*</sup>Centering plug required. Raptor's plug RWP-PLUG-208, sold separately, may need to be modified.

#### Universal Adapter 11.95" Diameter, 2" Height

Has multiple slots to allow for use on multiple machine pallets or rotary tables. This universal adapter is modular in design with many options

Material 7075 Aluminum with Black Anodized Finish

Product Height 2.0" / 50.8mm

Product Diameter 11.950" / 303.53mm

Bolt Circle Diameter T-Slots for 1/2" or M12 SHCS on

6.00"-10.00"/152.4mm-254mm B.C.


Connection Bolts (4) 1/2"-13 UNC-2B

Boss / Plug 1.250" Dia x 0.30" Receiving Hole Connects to RWP-224, RWP-601, RWP-602 Mounts All Fixtures with Raptor interface

\*Centering plug required. Raptor's plug RWP-PLUG-208, sold separately, may need to be modified.



#### **RWP-223 Universal Adapter Configuration Options**



#### Riser

This riser can be used in a modular configuration when combined with the Universal Adapter: RWP-223.

Material 7075 Aluminum Product Height 6.0" / 152.4mm Product Diameter 11.950" / 303.53mm Bolt Circle Diameter 10.150" / 257.81mm Connection Bolts (4) 1/2"-13 SHCS

Boss / Hole 1.000" Dia. X .300" Receiving Hole

Connects to Any Machine, RWP-223

Mounts All Fixtures with Raptor interface

\*Centering Plug required, RWP-PLUG-208, sold separately, may need to be modified.



#### **RWP-228**

#### Riser

While supplies last. Replaced by Universal Riser RWP-262. Enables compatible fixtures to be mounted on the pallet of the DMG Mori DMU50/50eco machine.

Material 7075 Aluminum Product Height 3.494" / 88.7476mm Product Diameter 8.96" / 227.584mm Bolt Circle Diameter 7.015" / 178.181mm Connection Bolts (4) M12 SHCS

> Boss / Hole 1.180" Dia x .250" Boss Connects to DMG Mori DMU50/50eco Mounts All Fixtures with Raptor interface



#### **RWP-234**

Riser

Enables compatible fixtures to be mounted on the Haas UMC-750 / UMC-750SS or Matsuursa MX-520 300MM.

> Material 7075-T6511 Aluminum Product Height 4.50" / 114.3 mm Product Diameter 11.40" / 289.56 Bolt Circle Diameter 9.92" / 251.968 mm Connection Bolts (4) M12 SHCS

> > Boss / Hole 1.970" Dia. x .750" Receiving Hole

Connects to Haas UMC-750 / UMC-750SS or Matsuursa MX-520 500MM



# **RWP-237**

#### **Nest Riser**

The RWP-237 is an aluminum Nest riser, designed for the Haas UMC-750 / UMC-750SS or Matsuursa MX-520 300MM.

> Material 7075-T6511 Aluminum Product Height 6.550" / 166.37mm Product Diameter 14.75" / 374.65mm Bolt Circle Diameter 13.20" / 335.28mm Connection Bolts (8) 1/2" SHCS

> > Boss / Hole 1.970" Dia x .750" Receiving Hole

Connects to Haas UMC-750 / UMC-750SS or Matsuursa MX-520 500MM

Mounts All Fixtures with Raptor interface



### **RWP-238-8**

#### **Adapter 8 Thread**

Aluminum Adapter to connect RWP-003 5C Rotary Indexer Spindle Nose 8TPI.

> Material 7075 Aluminum 5C Rotary Indexer Machine Type RWP-003 Connects to



# RWP-238-10

#### Adapter 10 Thread

Aluminum Adapter to connect RWP-003 5C Rotary Indexer Spindle Nose 10TPI.

> Material 7075 Aluminum 5C Rotary Indexer Machine Type RWP-003 Connects to

## **RWP-241**

#### **Adapter**

This adapter has the mounting interface for the RWP-027, 1.5" dovetail fixture, and is designed for the Yukiwa TNT100L.

Material 7075-T6511 Aluminum Product Height 0.75" / 166.37mm Product Diameter 3.938" / 374.65mm Bolt Circle Diameter 2.677" / 68mm Connection Bolts (4) M8 SHCS Boss / Hole 1.968" Dia x 0.230"

Machine Type Yukiwa TNT100L Fixture Compatibility RWP-027





# **RWP-601**

#### Aluminum Extender 1" Height

The 1" Extender is to add height when used with either Universal Adapter: RWP-222 or RWP-223 in lieu of using a riser.



Connects to Boss / Plug

Material 7075 Aluminum RWP-222, RWP-223 1.25" Dia x 0.25 31.75mm Dia x 6.35mm 

# **RWP-602**

#### Aluminum Extender 2" Height


The 2" Extender is to add height when used with either Universal Adapter: RWP-222 or RWP-223 in lieu of using a riser.



# inch Block

# **PINCH BLOCKS**

The Pinch Block connects directly to a Raptor dovetail fixture and is designed to offer a quick solution for secondary or final operations. Allows for quick dovetail removal and part completion. Convenient size and shape. Simply tighten with T-Handle wrench. Available in three sizes



# **RWP-702**

**Aluminum Pinch Block** 

Utilizes a single 3/8-16 Socket Head Cap Screw to actuate it.

Material 7075-T6511 Aluminum

Product Dimensions 2.350" L x 2.950" W x 1.820" H

59.69mm x 74.93mm x 46.228mm

Dovetail Width 1.50" / 38.1mm

Fixture Compatibility RWP-001(SS), RWP-004, RWP-013(SS),

RWP-026, RWP-027, RWP-036SS

\*Screw and shim are included



# **RWP-703**

**Aluminum Pinch Block** 

Utilizes two 3/8-16 Socket Head Cap Screws to actuate it.

Material 7075-T6511 Aluminum

Product Dimensions 5" L x 2.950" W x 1.820" H

127mm x 74.93mm x 46.228mm

Dovetail Width 1.50" / 38.1mm

Fixture Compatibility RWP-001(SS), RWP-004, RWP-013(SS),

RWP-026, RWP-027, RWP-036SS

\*Screw and shim are included



# **RWP-704**

**Aluminum Pinch Block** 

Utilizes a single 3/8-16 Socket Head Cap Screw to actuate it.

Material 7075-T6511 Aluminum

Product Dimensions 2.350" L x 2.950" W x 1.820" H

59.69mm x 74.93mm x 46.228mm

Dovetail Width 0.75" / 38.1mm

Fixture Compatibility RWP-002(SS), RWP-015, RWP-023, RWP-030SS,

RWP-034SS, RWP-038SS, RWP-405

\*Screw and shim are included



# The benefits of Raptors' workholding products are widespread!

Our customers have reported that by utilizing Raptor products in their facilities, there have been numerous benefits:

- Saving time and money by becoming more efficient.
- Ultimately increasing overall company health by:
  - \* Decreasing production time while increasing yield of finished goods
  - \* Opening up production schedules to accommodate more orders.
  - \* Improving employee performance by streamlining application processes, while increasing their enthusiasm and morale,
  - \* Growing their customer base due to greater production capacity, improving pricing and even increasing on-time delivery.

As we always say:

"Spend time making parts not figuring out how to hold them - Raptor is your solution!"

# **Policies & Warranty**

#### **Engineering Changes**

Specification and engineering data are subject to change without notice.

#### **Manufacturing Policy**

Products supplied by Raptor are high quality and adhere to manufacturing standards. Tolerances are uniformly held in accordance with catalog specifications. Our products are simple to use and we provide support material with each shipment to ensure that your applications go smoothly. We are happy to provide you with additional support, just contact us.

# **Damaged, Short or Lost Items**

UPS is our primary carrier. If your package and subsequent product is damaged/lost in transit, immediately place a claim with your UPS office. Keep all damaged product and packaging for inspection by UPS. Notify Raptor so we can help replace the merchandise.

#### **Returned Goods**

Materials cannot be returned without authorization. Final credit will be determined as follows:

- Only catalog items suitable for resale may be returned.
- Customers need to obtain an RGA# by contacting a Raptor Customer Service representative and reference the RGA# on the returned goods.
- Invoice number and date must be furnished.
- Follow packing instructions, if applicable, for returning goods.
- Transportation charges must be prepaid.
- Credit value will be issued at invoiced price less a minimum 20% restocking charge. Specials cannot be returned.

# **Warranty**

Raptor Products are protected with a 1 year limited warranty for parts\*

\* Subject to the terms as described in our Limited Warranty Policy.

<b>RWP-001</b> Aluminum 1.5" Dovetail Fixture	RWP-027 Aluminum 1.5" Dovetail Fixture 12
RWP-001SS Stainless Steel 1.5" Dovetail Fixture 11	RWP-030SS Stainless Steel 0.75" Dovetail Fixture 17
<b>RWP-002</b> 0.75" Dovetail Fixture	RWP-031SS Stainless Steel Dovetail Fixture 21
<b>RWP-002SS</b> 0.75" Dovetail Fixture	RWP-032SS Stainless Steel Dovetail Fixture 21
<b>RWP-003</b> Aluminum 0.75" Dovetail Fixture <b>14</b>	RWP-034SS Stainless Steel 0.75" Dovetail Fixture 17
■ RWP-003-4X Pyramid System	RWP-036SS Stainless Steel 1.5" Dovetail Fixture 12
<b>RWP-004</b> Aluminum 1.5" Dovetail Fixture	RWP-038SS Stainless Steel 0.75" Dovetail Fixture 18
<b>RWP-006</b> Aluminum 2.25" Dovetail Fixture	RWP-042-4X90T Mini Tombstone System 25
RWP-006SS Stainless Steel 2.25" Dovetail Fixture 10	RWP-042SS Stainless Steel 0.375" Dovetail Fixture 20
RWP-007SS Stainless Steel 0.75" Dovetail Fixture 15	<b>RWP-1027</b> Soft Jaw (Right)
RWP-011SS Stainless Steel 0.75" Dovetail Fixture 15	<b>RWP-1027-ST</b> Soft Jaw (Right)
RWP-012SS Stainless Steel 0.75" Dovetail Fixture 15	<b>RWP-1027-ST</b> Soft Jaw (Right)
<b>RWP-013</b> Aluminum 1.5" Dovetail Fixture	<b>RWP-1028</b> Soft Jaw (Left)
RWP-013SS Stainless Steel 1.5" Dovetail Fixture 11	<b>RWP-1028-ST</b> Soft Jaw (Left)
<b>RWP-015</b> Aluminum 0.75" Dovetail Fixture <b>16</b>	<b>RWP-1050</b> Serrated 45° Dovetail
RWP-017SS Stainless Steel 0.50" Dovetail Fixture 19	<b>RWP-1051</b> Standard Parallel (1/8" Ledge)
<b>RWP-018</b> Aluminum 0.50" Dovetail Fixture <b>19</b>	<b>RWP-1052</b> Thin Parallel (1/16" Ledge)
RWP-018SS Stainless Steel 0.50" Dovetail Fixture 19	<b>RWP-1056</b> Straight Edge 60° Dovetail
<b>RWP-019-4X45T</b> Pyramid System	<b>RWP-1527</b> Soft Jaw (Right)
<b>RWP-019-4X90T</b> Mini Tombstone System	<b>RWP-1527-ST</b> Soft Jaw (Right)
RWP-019SS Stainless Steel 0.375" Dovetail Fixture 20	<b>RWP-1528</b> Soft Jaw (Left)
RWP-022SS Stainless Steel 0.50" Dovetail Fixture 19	<b>RWP-1528-ST</b> Soft Jaw (Left)
RWP-023 Aluminum 0.75" Dovetail Fixture: 16	<b>RWP-1550</b> Serrated 45° Dovetail
RWP-024 Aluminum 0.75" Dovetail Fixture 16	<b>RWP-1551</b> Standard Parallel (1/8" Ledge) <b>5</b>
RWP-024-2XR In-Line Bridge System	RWP-1556 Straight Edge 60° Dovetail
RWP-024-3XR In-Line Bridge System 26	<b>RWP-202</b> Adapter
RWP-024-4XR In-Line Bridge System 26	<b>RWP-203</b> Adapter
<b>RWP-024-6XC</b> Carousel	RWP-206 Riser for Mori Seiki NMV3000
RWP-024SS Stainless Steel 0.75" Dovetail Fixture 16	<b>RWP-208</b> Emergency Adapter
<b>RWP-025</b> Aluminum Rail	<b>RWP-209</b> Emergency Adapter
RWP-026 Aluminum 1.5" Dovetail Fixture 12	RWP-209-V100 Emergency Adapter 6

<b>RWP-213SS</b> Stainless Steel 0.75"	RWP-704 Aluminum Pinch Block		
RWP-214SS Stainless Steel 1.5" Adapter 20	RWP-8-32 8/32 x 1/4 Replacement Locating Pins 28		
RWP-222 Universal Adapter	■ RWP-8-32CLS 8/32 x 1/4 Replacement Locating Pins . 28		
RWP-222-V100 Universal Adapter 6	RWP-8-32MO Replacement Locating Pins 28		
RWP-223 Universal Adapter	■ RWP-DC403U 3 Flute Uncoated 0.75"		
<b>RWP-223-V100</b> Universal Adapter 6	<b>RWP-DC404C</b> 4 Flute Coated 0.75"		
<b>RWP-224</b> Riser	<b>RWP-DC405C</b> 4 Flute Coated 0.248"		
<b>RWP-228</b> Riser	<b>RWP-DC407C</b> 4 Flute Coated 0.35"		
<b>RWP-234</b> Riser	<b>RWP-DC408C</b> 4 Flute Coated 0.45"		
<b>RWP-237</b> Nest Riser	<b>RWP-DC409C</b> 4 Flute Coated 0.248"		
<b>RWP-238-10</b> Adapter 10 Thread	<b>RWP-DC410C</b> 4 Flute Coated 0.75"		
<b>RWP-238-8</b> Adapter 8 Thread	RWP-KIT-3001SQ Replacement Clamp Kit 28		
RWP-239 Small Machine Adapter	RWP-KIT-301SQ Replacement Clamp Kit 28		
<b>RWP-241</b> Adapter	RWP-KIT-302SQ Replacement Clamp Kit 28		
<b>RWP-242-V100</b> Riser Plate	RWP-KIT-303SQ Replacement Clamp Kit 28		
<b>RWP-244-V100</b> 2.25" Dovetail Connector Plate <b>7</b>	RWP-KIT-304SQ Replacement Clamp Kit 28		
RWP-248SS Stainless Steel 0.5" Adapter 20	RWP-KIT-305SQ Replacement Clamp Kit 28		
RWP-249SS Stainless Steel 0.5" Adapter 20	RWP-KIT-306SQ Replacement Clamp Kit 28		
<b>RWP-251-V100</b> 2.25" Dovetail Connector Plate <b>7</b>	RWP-KIT-307SQ Replacement Clamp Kit 28		
<b>RWP-262</b> Riser	■ RWP-PLUG-208		
<b>RWP-33020</b> Mitee-Bite End Stop			
RWP-33050 Mitee-Bite TalonGripTM			
<b>RWP-401-11</b> Aluminum 11" Rail with 1.5" Dovetail 13			
RWP-403SS-12 Stainless Steel 2.75" Dovetail Fixture . 10			
<b>RWP-405</b> Aluminum 8" Rail with 0.75" Dovetail <b>18</b>			
<b>RWP-502</b> 100mm Self Center Vise			
<b>RWP-505</b> 150mm Self Center Vise			
<b>RWP-601</b> Aluminum Extender	■ Vises ■ Cutters & Parts		
<b>RWP-602</b> Aluminum Extender	Dovetail Fixtures		
RWP-702 Aluminum Pinch Block	Multi-Fixtures     Pinch Blocks		
RWP-703 Aluminum Pinch Block			

# THE BEST IN THE BUSINESS JUST BECAME EVEN STRONGER!

TE-CO has entered into a partnership to bring Swiss engineering and 100% Swiss made high pressure coolant lines to the **United States.** 

OR + MERANHA-COOLING LINE®





The patented

# **PIRANHA COOLING LINE**

solves all cooling problems on chip-removing processing



Fits on all standard tool holders



Flexible and available in both ( $\frac{1}{2}$  and  $\frac{1}{4}$  inch)



Withstands pressures up to 80 bar



Versatile use (cooling and high pressure chip removal)



Cost-Effective



Long lifespan thanks to anodized coating



Light Weight



New Design



100% Swiss Engineered and Manufactured



#### THREADED CONNECTOR

#### GA-1/8"

Threaded Connector 1/8"



#### **GA-M10**

Threaded Connector M10



#### **GA-1/8" NPT**

Threaded Connector 1/8" NPT



#### **GA-M10x1**

Threaded Connector M10x1



#### GA-1/4"

Threaded Connector 1/4"



#### **GA-M12x1**

Threaded Connector M12x1



#### **GA-1/4" NPT**

Threaded Connector 1/4" NPT



#### GA-R1/8"-L

Threaded Connector R1/8" Long



#### GA-M8

Threaded Connector M8



#### GA-R

Threaded Connector Blank





#### GA-M8-L

Threaded Connector M8 Long



#### **SPACER**

#### D-12.5/28

Spacer 28mm



#### D-12.5/43

Spacer 43mm



#### D-12.5/70

Spacer 70mm





#### **NOZZLE**

RD-12.5-1.5

Round Nozzle Ø1.5mm



RD-12.5-3.5

Round Nozzle Ø3.5mm



RD-12.5-4.5

Round Nozzle Ø4.5mm



RD-12.5-5.5

Round Nozzle Ø5.5mm



RD-12.5-7/1.5

Round Nozzle Multi-Hole



SDK-12.5/90°

Special Nozzle Ø1.8mm / 90° Short





#### SDL-12.5/90°

Special Nozzle Ø1.8mm / 90° Long



#### SDK-12.5/60°

Special Nozzle Ø1.8mm / 60° Short



#### SDL-12.5/60°

Special Nozzle Ø1.8mm / 60° Long



#### FD-12.5-20

Flat Nozzle 20mm



#### **DISTRIBUTOR**

#### L-12.5

90° Elbow



#### Quatro-12.5

Quatro Distribution Block



#### T-12.5

T-Distributor



#### Y-12.5

Y-Distributor



#### H-12.5

Ball Valve 1/4"



#### **ACCESSORIES**

#### M-SW16

Nut SW16



#### D-SW16

Cap SW16



# Ring 12.5

O-Ring 1/4"



#### S-11/16

Hexagon Wrench



#### **CUSTOMIZED PRODUCTS**


Can be produced by request











#### **COOLING LINE STARTER KIT**

#### Set

#### **PCL-1/4 SET 1**

**Cooling Line Starter Kit** 

Piranha Cooling Line Starter Kit Content:

- 3 Spacer 28.0mm
- 3 Spacer 43.0mm
- 3 Spacer 70.0mm
- 1 Threaded Connector 1/4"
- 1 Threaded Connector 1/4" NPT
- 1 Threaded Connector 1/8" NPT
- 1 Threaded Connector M10x1
- 1 Threaded Connector M12x1
- 1 Round Nozzle Ø3.5mm
- 1 Round Nozzle Ø4.5mm

- 1 Round Nozzle Ø5.5mm
- 1 Special Nozzle Ø1.8/60° Short
- 1 Special Nozzle Ø1.8/60° Long
- 1 Special Nozzle Ø1.8/90° Short
- 1 Special Nozzle Ø1.8/90° Long
- 5 Nuts SW 16x7mm
- 1 90° Elbow
- 1 Y-Distributor
- 2 Hexagon Wrench SW11/SW16
- L x W x H 210 x 150 x 40mm



#### THREADED CONNECT-

#### **GA-22-3/8" NPT**

Threaded Connector 3/8" NPT



#### GA-22-3/8"

Threaded Connector 3/8"



#### GA-22-1/2" NPT

Threaded Connector 1/2" NPT



#### GA-22-1/2"

Threaded Connector 1/2"



# SPACER

#### D-22-46

Spacer 46.5mm



#### D-22-63

Spacer 63.5mm



#### D-22-80

Spacer 80mm



#### **NOZZLE**

#### RD-22-6

Round Nozzle Ø6mm



#### **RD-22-8**

Round Nozzle Ø8mm



#### RD-22-10

Round Nozzle Ø10mm



#### RD-22-12-19.2

Round Nozzle Ø10mm Multi-Hole



#### SDK-22/60°

Special Nozzle Multi-Hole / 60° Short



#### SDL-22/60°

Special Nozzle Multi-Hole / 60° Long



#### SDK-22/90°

Special Nozzle Multi-Hole / 90° Short



#### SDL-22/90°

Special Nozzle Multi-Hole / 90° Long



#### **DISTRIBUTOR**

L-1/2"

90° Elbow



**FLAT NOZZLE** 

FD-22-30

Flat Nozzle 30



T-1/2"

T-Distributor



FD-22-40

Flat Nozzle 40



Y-1/2"

Y-Distributor



FD-22-50

Flat Nozzle 50



Y-1/2"- 1/4"

Y-Distributor



FD-22-60

Flat Nozzle 60



H-22

Ball Valve 1/2"



FD-22-80

Flat Nozzle 80



**ACCESSORIES** 

M-SW27

Nut SW27



FD-22-100

Flat Nozzle 100



**D-SW27** 

Cap SW27



Ring 22

O-Ring 1/2"



S-21/27

Hexagon Wrench















100 Quinter Farm Road Union, OH 45322

Toll Free: 800-824-8333

www.raptorworkholding.com

**Contact Us:** 

www.info@raptorworkholding.com

# **NOTES**

# **NOTES**



# RaptorWorkholding.com



Patent No. US8,672,310 B2 Patent No. US9,126,299 B2